



Product data sheet

HLAY5BC42

Characteristics

Mushroom head push-button, HLAY5, mushroom 40 mm, 1 NC, red

	Main	
	Range of product	HLAY5
	Device presentation	Complete product
	Product or component type	Mushroom head push-button
	Bezel material	Metal
	Mounting diameter	22 mm
	Head type	Standard

Complementary

Cap/operator or lens colour	Red
Fixing collar material	Metal
Shape of signaling unit head	Round
Type of operator	Spring return
Operator profile	Red mushroom Ø 40 mm
Contacts type and composition	1 NC
Contact operation	Slow-break
Contacts usage	Standard contacts
Mechanical durability	1000000 cycles
Connections - terminals	Screw clamp terminals
[Ith] conventional free air thermal current	6 A
[Uimp] rated impulse withstand voltage	6 kV
[Ie] rated operational current	2 A at 380 V 3.3 A at 220 V, AC-15 0.5 A at 220 V 1.1 A at 110 V, DC-13
Electrical durability	1000000 cycles AC 200000 cycles DC
E-commerce address	Hlay5-pushbuttons-mushroom-and-emergency-stop-pushbuttons-1

Environment

Ambient air temperature for operation	-5...40 °C
IP degree of protection	IP40 IP65 with protective cover
Standards	IEC 60947-5-1

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Number of Units in Package 1	1
------------------------------	---

Offer Sustainability

Sustainable packaging	No
-----------------------	----